

MILOS 600 3*

Cylinders



Patented key section

200,000 differs

Six pin as standard

Comprehensive range of offset sizes available

Number of pin chambers

Six

Key Duplication

Multiple patented key sections, duplicate keys only available from UAP

BSI Kitemark

EN1303 Key Durability

Extensive Offset from 60mm up to 120mm

Cylinder range includes

RIM, THREADED, SCANDINAVIAN, EURO PROFILE DOUBLE & KEY/TURN

STANDARD

Conforms to the highest security standard of EN1303:2015

RANGE

An extensive range of Euro profile offset sizes in both Double and Key&turn variant, E

FINISH

Available in a range of finishes, Satin Nickel, Brass, Polished Chrome, Black.



SACRIFICIAL CUT AS STANDARD



The cylinder has a sacrificial cut, so when force is applied to either end, the cylinder will break away to the sacrificial cut line only, leaving the remaining cylinder operational and the locking mechanism intact.

ANTI DRILL AS STANDARD



Hardened steel anti-drill pins are in each side of the cylinder.
Plus all body pins are nickel plated hardened steel 50 HRC minimum.

ANTI PICK AS STANDARD



Minimum of 4 anti-pick pins in each side of the cylinder makes it extremely difficult for a common burglar to pick the cylinder.

ANTI BUMP AS STANDARD



The cylinder has a unique anti-bump system.



	MILOS 600 3*	MILOS 600	MILOS 100R	MILOS 100
Patented Key System	Y	Y	N	N
Restricted Key Duplication	N	N	Y	N
Unrestricted Key Duplication	N	N	N	Y
No. of Pins	6	6	6	6
Suitable for Simple Masterkeying	Y	Y	Y	Y
Suitable for Complex Masterkeying	Y	Y	N	N
TS007 3 Star	Y	N	N	N
TS007 1 Star	N	N	Y	Y
Classroom Function	N	Y	Y	Y
Anti-Barricade Function	N	Y	Y	Y
1, 2, 3 Function	N	Y	N	N
Key Override Function	N	Y	N	N
Construction Keying	N	Y	N	N
EN 1303 Grades	Y	Y	Y	Y
Sacrificial Cut As Standard	Y	N	Y	Y