

Notified Body No. 2812

## Certificate of Constancy of Performance

**2812-CPR-AG10550**

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

### Range of Mortice Sash Locks, Mortice Bathroom Locks & Mortice Latches See Annex A

**Intended use: For use on fire/smoke compartmentation doors**

Essential characteristics	Performance	Harmonised technical specification
<b>Mechanical test evidence: WIL 322574, WIL 322576, WIL 323440, WIL 323441, WIL 323442 &amp; WIL 542673</b> <b>Fire test evidence: WF 322626 &amp; WF 324016 iss.4</b>		
Self-closing 5.4.2 Closing force  5.1.2 Re-latching force of latch bolt	Grade 8 = 200Kg door mass with 15N maximum closing force.  >2.5N	<b>EN 12209:2003 / AC:2005</b>
Durability of self-closing 5.3.1 Durability of latch action	Grade X = 200,000 cycles with 120N side load on latch bolt.	
Ability to maintain the door in the closed position and not contribute to its spread of fire 5.2.1 Resistance to side load on latch bolt	Grade 3: 3kN	
5.5 Suitability for use on fire/smoke doors	Grade 1: suitable for use on fire/smoke resistant door assemblies	
Control of dangerous substances 5.1.1 Dangerous substances	Pass: The materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Notified Body No. 2812

## Certificate of Constancy of Performance

**2812-CPR-AG10550**

Placed on the market under the name of:

**UAP Limited  
Orbital 60  
Dumers Lane  
Bury  
BL9 9UE  
United Kingdom**

and produced in the manufacturing plant:

**CUY82045-12**

**This is coded format, and the information is held by the Notified Body.**

This certificate attests that all provisions concerning the Assessment and Verification of Constancy of Performance described in Annex ZA of the standard(s):

**EN 12209:2003 / AC:2005**

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **09/09/2025** and will remain valid as long as neither the harmonised standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

Valid to: **08/11/2027**

ERO Project Reference: **ERO 034621 P2964**



**Pascal Coget  
General Manager – European Certification**

CSF408-NL 8.0

Notified Body No. 2812

## Certificate of Constancy of Performance

### 2812-CPR-AG10550

#### Annex A

UAP Model No.	Description	Backset	Centres
LL-11.861.SSS LL-11.861R.SSS	72mm Mortice sashlock Square or radiused forend	40mm 45mm 50mm 55mm 60mm 65mm 70mm 80mm	72mm
A85Z-40 A85Z-45 A85Z-50 A85Z-60 A85Z-80	85mm Mortice sashlock Square or radiused forend	40mm 45mm 50mm 60mm 80mm	85mm
A72ZN-45 A72ZN-50 A72ZN-55 A72ZN-60 A72ZN-65	72mm Mortice night latch Square or radiused forend	45mm 50mm 55mm 60mm 65mm	72mm
LL-13.862.SSS LL-13.862R.SSS	78mm Mortice bathroom lock Square or radiused forend	45mm 50mm 55mm 60mm 65mm	78mm
LL-13.861.SSS LL-13.861R.SSS	72mm Mortice passage latch Square or radiused forend	40mm 45mm 50mm 55mm 60mm 65mm 70mm 80mm	72mm
A55ZL	72mm Mortice latch Square or radiused forend	55mm	72mm

20mm to 24mm width, square or radius forend in various finishes including the following:

**SSS**  
**PSS**  
**PVD**

**Satin stainless steel**  
**Polished stainless steel**  
**PVD brass**

**BLACK**  
**BRZ**

**Black finish**  
**Bronze finish**