

## **CONSTRUCTION PRODUCTS REGULATION 2011 DECLARATION OF PERFORMANCE**

**DoP Number:** IH-DCL-CAMCON-11205– Issue 1

**1. Unique identification of the product type:**

Controlled door closing Devices

**2. Type, batch or serial number or any other element allowing identification of the construction product as required under Article 11(4) of the CPR:**

IH-DCL-CAMCON-11205

**3. Intended use or uses of the construction product, in accordance with the applicable harmonised technical specification, as foreseen by the manufacturer**

For use on fire and smoke compartmentation doors and escape route doors, when fitted in accordance with the manufacturers fitting instructions

**4. Name, registered trade name or registered trade mark and contact address of the manufacturer as required under Article 11(5):**

UAP Limited, Orbital 60, Durers Lane, Bury, Greater Manchester, Uni, BL9 9UE

**5. Where applicable, name and contact address of the authorised representative whose mandate covers the tasks specified in Article 12(2):**

N/A

**6. System or systems of assessment and verification of constancy of performance of the construction product as set out in CPR, Annex V:**

SYSTEM 1

**7. In case of the declaration of performance concerning a construction product covered by a harmonised standard please give the Notified Body Number:**

**EN 1154: 1996: A1: 2002/AC:2006**

**Notified product certification body No:** 2812 performed the type testing and issued test reports.

**Certificate of Constancy of Performance:** 2812-CPR-AD10510

**8. European Technical Assessment:**

N/A

Fire

Security

Innovation

## 9. Declared Performance

Essential characteristic Self closing	Performance	Harmonised technical specification
<b>5.2.1 General</b>		EN1154:1996: A1:2002/AC:2006
<b>Application</b>	Concealed in the Door	
<b>5.2.2 Durability</b>	500,000 test cycles	
<b>5.2.3 Closing moment</b>	Pass size 2 - 5	
<b>5.2.4 Opening moment</b>	Pass size 2 - 5	
<b>5.2.5 Efficiency;</b>	More than 50% size 2 More than 55% size 3 More than 60% size 4 More than 65% size 5	
<b>5.2.6 Closing time</b>	Pass- After 5K and 500K test cycles, the closing time from an opening angle of 90° was capable of adjustment to 3 s or less, and 20 s or more- After 500K test cycles, the closing time set at 5K test cycles did not increase by more than 100%, or decrease by more than 30%.	
<b>5.2.7 Angles of operation</b>	Grade 3, 105°	
<b>5.2.8 Overload performance</b>	Pass - The closer withstood the closing overload tests	
<b>5.2.9 Temperature dependence</b>	-15°C to +40°C	
<b>5.2.10 Fluid leakage</b>	Pass - There was no leakage of fluid from the closer	
<b>5.2.11 Damage</b>	Pass - There was no damage to the door closing device that would adversely affect its performance to the standard	
<b>5.2.12 Latch control</b>	Pass - Effective over max. range of 15° from closed position, and adjustable	
<b>5.2.13 Backcheck</b>	N/A	
<b>5.2.14 Delayed closing</b>	N/A	
<b>5.2.15 Adjustable closing force</b>	Pass	
<b>5.2.16 Zero position (Double action only)</b>	N/A	
<b>5.2.18 Fire / smoke doors</b>	Grade 1: Suitable for use on fire/smoke door assemblies	
<b>5.2.2 Durability</b>	Grade 8 500,000 test cycles	
<b>5.2.17.1 Corrosion</b>	Grade 3 : 96 hrs	
<b>5.2.17.2 Corrosion</b>	Pass - After the salt spray test, the closing moment of the door closer was not less than 80% of that measured prior to the test.	
<b>Dangerous Substances Annex ZA3</b>	The materials in the product do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations.	

Fire

Security

Innovation

10. The performance of the product identified in points 1 and 2 as in conformity with the declared performance in point 9.

This declaration of performance is issued under the sole responsibility of the manufacturer identified in point 4.



Signed for and on behalf of the manufacturer at:

UAP Limited, Orbital 60, Dumers Lane, Bury, Greater Manchester, United Kingdom, BL9 9UE

Dated: 23<sup>rd</sup> May 2025

Fire

Security

Innovation