

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AG10551

In compliance with *Regulation 305/2011/EU of the European Parliament and of the Council of 9 March 2011* (the Construction Products Regulation or CPR), this certificate applies to the construction product:

Range of Mortice Deadlocks See Annex A

Intended use: For use on fire/smoke compartmentation doors

Essential characteristics	Performance	Harmonised technical specification
Mechanical test evidence: WIL 322574, WIL 323443 & WIL 542673 Fire test evidence: WF 322626 & WF 324016 iss.4		
Self-closing 5.4.2 Closing force	NPD	EN 12209:2003 / AC:2005
5.1.2 Re-latching force of latch bolt	NPD	
Durability of self-closing 5.3.1 Durability of latch action	NPD	
Ability to maintain the door in the closed position and not contribute to its spread of fire 5.2.1 Resistance to side load on latch bolt	NPD	
5.5 Suitability for use on fire/smoke doors	Grade 1: suitable for use on fire/smoke resistant door assemblies	
Control of dangerous substances 5.1.1 Dangerous substances	Pass: The materials in the lock do not contain or release any dangerous substances in excess of the maximum levels specified in existing European material standards or any national regulations (1)	

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AG10551

Placed on the market under the name of:

Allegion Safety & Security Solutions Limited

Orbital 60

Dumers Lane

Bury

BL9 9UE

United Kingdom

and produced in the manufacturing plant:

E018761-1

This is coded format, and the information is held by the Notified Body.

This certificate attests that all provisions concerning the Assessment and Verification of Constancy of Performance described in Annex ZA of the standard(s):

EN 12209:2003 / AC:2005

Under System 1 for the performance set out in this certificate are applied and that the Factory Production Control conducted by the manufacturer is assessed to ensure the constancy of performance of the construction product.

This certificate was first issued on **09/09/2025** and revised on **17/06/2026** and will remain valid as long as neither the harmonised standard, the Construction Product, the AVCP methods nor the manufacturing conditions in the plant are modified significantly, or unless suspended or withdrawn by the Notified Product Certification Body.

Valid to: **08/11/2027**

ERO Project Reference: **ERO 034621 P3355**



Paul Duggan
Certification Manager

CSF408-NL 8.0

Notified Body No. 2812

Certificate of Constancy of Performance

2812-CPR-AG10551

Annex A

UAP Model No.	Description	Backset
A55ZD	72mm Mortice dead lock Square or radiused forend	55mm
LL-12.851.SSS LL-12.851R.SSS	72mm Mortice dead lock Square or radiused forend	40mm 45mm 50mm 55mm 60mm 65mm 70mm 80mm

20mm to 24mm width, square or radius forend in various finishes including the following:

SSS
PSS
PVD

Satin stainless steel
Polished stainless steel
PVD brass

BLACK
BRZ

Black finish
Bronze finish